TANKJET 9 TANK CLEANING NOZZLE FEATURES AND BENEFITS

- Multiple flat spray nozzles are mounted in a rotating spray head that is driven by the flow of the cleaning liquid
- Simple and reliable, with no ball bearings, tank cleaners operate effectively in any position, vertical or horizontal
- Well-suited to clean-in-place and sanitary applications, chemical distribution and passivation
- Offered in three versions for medium-size tanks:
 - TankJet 9-A features two flat side sprays, each covering 175°
 - The TankJet 9-B and 9-C versions each have six flat sprays and provide coverage of the entire tank

TankJet 9-B tank cleaning nozzle, see page D20



TankJet 9-A Tank Cleaning Nozzle						
Max. tank diameter:	6 ft. (1.8 m)					
Operating principle:	Fluid-driven reactionary force					
Flow rate:	1.3 to 5 gpm (4.9 to 18.9 lpm)					
Operating pressure:	10 to 120 psi (0.7 to 8.3 bar)					
Max. temperature:	190°F (88°C)					
Materials:	Bearings – Carbon filled PTFE fluoropolymer All other metallurgy – 316 stainless steel					
Inlet connection:	3/8" NPT or BSPT (F)					
Optional accessories:	Strainers, recommended mesh size: 20 (840 micron) See page G2					

Spraying Systems Co. TankJet® TJ9-A

TankJet 9-A tank cleaning nozzle





Vertical

Horizontal

45° Up

45° Down 🗡 🌂

≜|↓

← →

XX

R

RINSING



IDEAL FOR CLEANING:

Brewery tanks

TankJet 9-C tank cleaning nozzle, see page D20

T19-B


- Chemical containers
- Drums and kegs
- Food processing tanks
- Pharmaceutical tanks
- Wine barrels and vats

For lances, mounting kits, adapters and more, see page G6



TANK DIA. **6 ft.** (4.9 m)

PERFORMANCE DATA



Model		Model Type	Liquid Flow Capacity gpm (lpm)							
	odel		10 psi (0.7 bar)	30 psi (2.1 bar)	50 psi (3.4 bar)	70 psi (4.8 bar)	90 psi (6.2 bar)	100 psi (7.0 bar)	110 psi (7.6 bar)	120 psi (8.3 bar)
T	19	А	1.3 (4.9)	2.5 (9.5)	3.0 (11.4)	4.0 (15.1)	4.5 (17)	4.7 (17.8)	4.9 (18.5)	5.0 (18.9)

ADDITIONAL SIZES AVAILABLE

TankJet 9-B & 9-C see page D20

DIMENSIONS AND WEIGHTS

TankJet 9 Tank Cleaning Nozzle	L	W	Min. tank opening	Weight
	in. (mm)	in. (mm)	in. (mm)	Ibs. (kg)
	2.31 (59)	1.06 (27)	1.25 (32)	0.34 (0.15)

Additional sizes available: Page D20 – 1/2 and 3/4 in. conn.

ORDERING INFORMATION TANKJET 9-A TANK CLEANING NOZZLE



* Leave blank for NPT connection or insert B for BSPT connection.

